

# Wireless HD Emergency PTZ Camera(Model-C)



## Main Feature

- ※ Integrated structure design, protection level IP66
- ※ 2.1 MP starlight class HD movement, optional 4K ultra-clear movement
- ※ 100m IR night vision, can realize day and night deployment
- ※ 360° omnidirectional PTZ, support 3D centering zoom function
- ※ Support 4G/5G remote wireless video transmission, real-time smooth image
- ※ Dual TF card storage, single card can support up to 256G
- ※ Built-in large-capacity lithium battery, can work continuously for more than 10 hours
- ※ Built-in OLED screen, real-time display of working status
- ※ Supports Bluetooth communication to realize two-way intercom and cluster intercom
- ※ Support Beidou/GPS dual-mode positioning, built-in antenna

Wireless HD Emergency PTZ Camera (Model-C) is a portable terminal built for wireless HD emergency monitoring needs, which supports 4G transmission, remote video, intercom, positioning and other functions. The product assists users in daily visual inspection, mobile law enforcement monitoring, emergency command and dispatch and other business management.

## Application Industry



Public Security



Traffic



Court



Urban Management



Emergency Management



Fire Fighting



Armed Police



Civil Air Defence



Safety Supervision



Electric Power



Construction Site



Activity Security

## Product Parameters

Model		TSP260-C
Movement	Lens	High-quality HD integrated movement
	WDR	Support
	Optical Zoom	30×
	Digital Zoom	16×
	Low Illumination	Starlight class movement
PTZ	Horizontal Rotation	360°
	Vertical Rotation	-15° ~ 90°
Video	Compression Standard	H.265/H.264
	Resolution	1080P/720P etc.
	Frame Ratio	1 ~ 30 fps adjustable
	Bit Stream	Support dual stream
Audio	Type	Support external Bluetooth headset, Bluetooth hand microphone, wired hand microphone
Storage	TF Card	Dual TF card storage
Wireless	Mobile Network	4G all network
	WiFi	802.11a/b/g etc.
	Bluetooth	Support
Positioning	Module	Built-in positioning module supports Beidou, GPS hybrid positioning
Others	Protection Level	IP66
	Size	Φ156(mm)×230(mm)
	Working Temp. & Humidity	-20°C ~ 60°C; <95%

## Product Model

Model	Description
TSP260-C-LA2-1H-J14	Dual 4G version