


Wireless Vehicle-mounted DVR



Main Feature

- ※ Adapt to all network, multi-card binding, support 4G/3G/WiFi/AP
- ※ Multi-channel digital HD or analog HD input, 1080P/720P and other resolutions are optional
- ※ Support two-way video intercom
- ※ Support cluster call, cluster scheduling, call recording, scheduling instructions issued
- ※ Front-end patented storage technology ensures the safety and reliability of hard disk recording, and supports local video playback output
- ※ Support hard disk storage and SD card storage
- ※ 8-36 volt wide voltage design, 12 volt camera power supply constant voltage output
- ※ Beidou/GPS dual-mode positioning, synchronous storage of positioning information
- ※ Support Tsinglink iCVS cloud video management platform, command center dedicated dispatch platform

The product is a vehicle-mounted or shipborne mobile terminal that integrates high-definition video storage, transmission, two-way intercom, HD video recording, three ways of positioning (Beidou/GPS/base station), cluster intercom, and emergency command.

Application Industry



Passenger Traffic



Bus



School Bus



Taxi



Armed Escort



Dangerous Goods Vehicle



Muck Truck



Logistics



Urban Management



Road Administration



Public Security



Traffic Police

Product Parameters

Model		TSM610-B	TSM610-C
Video	Compression Standard	H.264, H.265	
	Input	8 channel network input, aviation interface	4 channel AHD simulation, aviation interface
	Output	1 channel VGA output; 1 channel CVBS output	1 channel VGA output; 1 channel CVBS output
	Resolution	1080P, 720P etc.	1080P
	Frame Ratio	1 ~ 25 fps adjustable	
	Bit Rate	Support dual stream, 64kbps ~ 8Mbps adjustable	Support dual stream, 64kbps ~ 4Mbps adjustable
Audio	Audio	8 channel input	4 channel input
	Intercom	Two-way intercom, support hand microphone	
Storage	SD Card	Support	Dual SD cards storage
	Hard Disk	Pull-out hard disk storage, 2.5-inch hard disk, up to 4T	/
Extensions	Intelligent Application	Support license plate recognition	/
Wireless	Network	WCDMA, EVDO, TD-SCDMA, TDD-LTE, FDD-LTE	
	WiFi	802.11a/b/g 2.4G etc.	
Positioning	Module	Built-in positioning module, supporting Beidou, GPS hybrid positioning	
Power Supply	Input	8-36V wide power input, with short connection, reverse connection, overcurrent protection	
	Output	DC 12V constant voltage output	
Operation	Remote Control	Support OSD menu remote operation	
	Mouse & Keyboard	Support mouse and keyboard operation	
Others	Size	235mm×190mm×80mm	132mm×137mm×40mm
	Working Temp. & Humidity	-20°C ~ 50°C, 10% ~ 90%	

Product Model

Model	Description
TSM610-B-LAx-8N-W	8 channel network HD video transmission, dual 4G version
TSM610-C-LAx-4HA-W	4 channel analog HD video transmission, 4G version