

Intelligent Bullet IP Camera



Main Feature

- ※ Support 1080P/720P/VGA and other resolutions
- ※ Maximum support 2 channel 1920×1080@30 frame stream at the same time
- ※ Support encoding H.265 compatible with H.264
- ※ Support electric zoom, optional 3.6~10mm or 9~22mm
- ※ Support audio, alarm input and output
- ※ Embedded safety helmet detection feature algorithm
- ※ Embedded face recognition algorithm
- ※ 2 dot matrix lights, infrared distance is 60 meters
- ※ Support Tsinglink iCVS2.0 cloud platform
- ※ Support iCAP protocol

Intelligent Bullet IP Camera is an infrared waterproof intelligent terminal for indoor and outdoor fixed points. The product can improve the user's real-time visual intelligent monitoring and management ability, has HD video transmission, safety helmet detection, face detection and recognition, voice broadcast, alarm input and output and other functions, can be widely used in intelligent construction site, intelligent community, intelligent park, substation and other occasions, and can provide customized services for the development of intelligent algorithms for application scenarios.

Application Industry



Construction Site



Substation



Community



Park



Railway



Mining



Water Conservancy



Highway



Forest



Scenic



Environment Protection



Public Security

Product Parameters

| Model | | TSC620-B |
|--------------|----------------------|-----------------------------------------------------------------|
| Camera | Sensor | 1/2"SONY Progressive Scan CMOS |
| | Lens | Support electric focus |
| | RTC | Support, time will not be lost when power is off |
| Video | Compression Standard | H.265, compatible with H.264 |
| | Resolution | 1080P/720P/VGA etc. |
| | Frame Ratio | 1~30 fps adjustable |
| | Bit Stream | Support dual stream |
| Capture | Format | JPEG |
| | Resolution | 1080P/720P/VGA etc. |
| | Overlay | Support overlay time, name information |
| Audio | Input | One channel audio input |
| | Output | One channel audio output |
| Network | Ethernet | RJ45 waterproof pigtail cable 10M / 100M adaptive Ethernet port |
| Alarm | Input | One channel alarm input |
| | Output | One channel alarm output |
| Serial Port | RS485 | One channel RS485 |
| Power Supply | Input | DC12V |
| | Interface | DC5.5 |
| Others | Installation Method | Wall, ceiling installation |
| | Size | 313mm(L)×101mm(W)×70mm(H) |
| | Working Temperature | -10°C~50°C |
| | Working Humidity | 0%~85% |

Product Model

| Model | Description |
|--------------------|-------------------------------------------------------|
| TSC620-B-1H-R6-IZ3 | HD infrared waterproof camera, 3.6~10mm electric lens |
| TSC620-B-1H-R6-IZ4 | HD infrared waterproof camera, 9~22mm electric lens |